

PRE3207B-PRM

Miniature flush or surface-mounted ceiling PIR detector



Cleverly simple
control of energy.



Key features

- 230V AC 50Hz
- 6A incandescent & fluorescent lighting
- 3A Compact fluorescent, LED lighting and fans, ventilation equipment
- Miniature PIR head surface or flush mount
- Mounting heights up to 7m
- Detection range of up to 9m at 2.8m ceiling height
- Lux light level detection
- 10 second to 99-minute timing range
- Easy connection to the power supply via RJ11 plug
- Slimline power supply available on request
- Digital and analogue dimming versions available on request
- Tamperproof infra-red setup via PRE5901 or 5903 handsets
- 5-year warranty
- IP40
- EMC-2014/30/EU, LVD-2014/45/EU

The PRE3207B-PRM is a miniature PIR presence detector.

The sensor head can be flush mounted or surface-mounted.

Using the end cap accessory the PIR head can be mounted directly to a luminaire or metal enclosure.

The PRE3207B-PRM is powered by a separate power supply, this is easily connected to the PIR head through the use of the RJ11 connector.

This unit is also available as a dimming variant for digital DALI or DSI fittings or analogue 1-10V dimming.

The Powerful PIR head can be mounted up to 9m from floor level, at this height the PIR has a detection range on the floor of 16m².

Due to our policy of continuous improvement, we reserve the right to change specifications without notice.
All information was correct at time of when this product file was produced - June 2020