

# PRE3205-DD

## Direct digital dimming ceiling-mounted IR settable photocell



### Key features

- Supply voltage - 220-240 Volts AC 50Hz
- Load - 10A resistive, incandescent, fluorescent, compact fluorescent, low energy lighting, low voltage lighting switching primary of the transformer,
- Light level - Adjustment 100 LUX to 1000 LUX approx.
- Timing range 10 seconds to 99 minutes
- Terminal capacity - 2.5mm<sup>2</sup>
- Material - Flame retardant ABS, fixing clip polypropylene
- Type - Class 2
- Temperature - -10°C to 35°C
- Conformity - EMC-2004/108EC LVD-2006/95/EC IP40
- 5-year warranty

## The PRE3205-DD dimming photocell automatically adjusts the light output of luminaires depending on the amount of natural light available, to a maintained illuminance level.

The PRE3205-DD photocell will turn lighting on when the ambient light falls below a preset level. The lighting will then be turned off when the total light level rises above a separate preset level. The unit also has a switch input for manual override when required.

This product has an integral sensitivity and time adjustment. All timings, light levels, and all other parameters are programmed via the PRE5901 or PRE5903 programming handsets. Once programmed the parameters are fully tamperproof. One handset will program all PRE3205 sensors and a selection of other Prefect products.

The PRE3205-DD supports direct digital dimming, switchable between DALI and DSI systems (Handset required not supplied, See PRE5901 & PRE5903).

For 1-10V analogue dimming see the PRE3205-AD.

Due to our policy of continuous improvement, we reserve the right to change specifications without notice. All information was correct at time of when this product file was produced - June 2020